



## OPTIONAL ACCESSORIES

Sheet P.32

### CB

Threaded pulse launcher meter

Rev. 0 - 03/24



### CHARACTERISTICS



Woltmann-type reel-mounted CB series meters for horizontal and vertical mounting with direct reading.

Available with 1/2" - 2" connections, they can be used with cold water, max. 30°C.

The case and the head are made of brass while the mechanisms and rollers are made of anti-groscopic, anti-magnetic and anti-scaling plastic; CB series meters are supplied in the standard 4 pulses/liter version.




### TECHNICAL DATA

Code	9900400001	9900400002	9900400003	9900400004	9900400005	9900400015
Model	CB 1/2"	CB 3/4"	CB 1"	CB 1" 1/4	CB 1" 1/2	CB 2"
Connections	1/2"	3/4"	1"	1" 1/4	1" 1/2	2"
Pulses per liter L	4/1					
Working pressure Bar	16					
Nominal flow rate m <sup>3</sup> /h	1,5	2,5	3,5	5,0	10,0	15,0
Min.-Max. flow rate - m <sup>3</sup> /h	0,03 - 3,0	0,05 - 5,0	0,08 - 7,0	0,12 - 10,0	0,20 - 20,0	0,31 - 30,0
Protection class	IP 64					



### OVERALL DIMENSIONS



Code	A	B	C
	mm	mm	mm
9900400001	110/165	90	80
9900400002	130/190	90	100
9900400003	260/160	120	100
9900400004	260/160	120	120
9900400005	300/200	130	140
9900400015	300	200	160

### AVERAGE DELIVERY TIMES

1 week