



WE

Flanged pulse launcher meter

Rev. 0 - 03/24



CHARACTERISTICS



WE series Woltmann type reel meters for horizontal and vertical mounting with direct reading.

Available with DN 50 - DN 80 connections and they can be used with cold water; max 30°C.

The case and the head are made of cast iron painted externally; WE series meters are supplied in the standard version with 1 pulse every 100 liters.

The WE meter can also be supplied in the 1 pulse every 10 liters version.




TECHNICAL DATA

Code	9900424063	9900424066	9900424069	9900424072	9900424074	9900424077
Model	WE 50	WE 65	WE 80	WE 100	WE 125	WE 150
Connections DN	DN50	DN65	DN80	DN100	DN125	DN150
Number of flange holes	4			8		
Pulses per liter L	1/100					
Working pressure Bar	16					
Nominal flow rate m³/h	40	63		100	160	250
Min./Max. flow rate m³/h	0,50 - 50,0	0,78 - 78,0		1,25 - 125,0	2,0 - 200,0	3,1 - 312,0
Protection class	IP 64					



OVERALL DIMENSIONS



Code	A	B
	mm	mm
9900424063	200	247
9900424066	200	258
9900424069	225	265
9900424072	250	272
9900424074	250	292
9900424077	300	302

AVERAGE DELIVERY TIMES

1 week